

# VISIO-DRIVE-CONTROL II



# VISIO-DRIVE-CONTROL II

## Type 63.202 / 64.102



### PRODUCT FEATURES:

- Top performance in combination with electric HEITEC VISIO-DRIVE linear motors and SYNCHRO drive systems
- 100% monitored and controlled process
- Intuitive, easy operation via touch screen
- Positioning accuracy of the valve pins: 0.01 mm
- Optimised calibration process recognises blockages and contamination when approaching the mould without damaging the valve pins. Freely adjustable forces, speeds and travel profiles
- Special travel profile that minimises wear in the gate
- High process reliability thanks to freely programmable warning and cut-out thresholds of the drive system
- Networking between drive controller, injection moulding machine and temperature controller prevents operator errors (moving pins when hot runner system is cold, etc....)
- Can also be used for the actuation of core pullers, ejectors or mould sliders.

### VISIO-LINEAR-DRIVE 5000



### VISIO-LINEAR-DRIVE Typ 64.102.01

Type	VLD 5000	VLD 10000	VLD 15000
Needle diameter	Number of needles	Number of needles	Number of needles
	max.	max.	max.
Ø 2,5	24	48	60
Ø 3	16	32	48
Ø 4	12	24	36
Ø 6	8	16	24

